

# 800G OSFP RHS 2LR4 10km

## CL800GOSFP2LR4-RHS

### Product Features:

- Compliant with IEEE 802.3cu-2021
- 2x400GBASE-FR4 optical interface
- Compliant with IEEE P802.3ck D3.0
- - 2x400GAUI-4 C2M electrical interface
- Compliant with OSFP MSA HW Rev 4.1
- Type 2 housing with dual LC connector
- Compliant with CMIS Rev 5.0
- Case operating temperature 0°C to 70°C
- Two wire serial Interface with digital diagnostic monitoring
- Complies with EU Directive 2011/65/EU (RoHS compliant)
- Class 1 Laser

### Functional Characteristics (Optical)

The following tables list the performance specifications for the various functional blocks of the integrated optical transceiver module.

**Table 1 – Transmitter Optical Specifications**

Parameter	Symbol	Min.	Typical	Max.	Unit	Notes
Wavelength L0, L4	$\lambda_{C0}, \lambda_{C4}$	1264.5	1271	1277.5	nm	
Wavelength L1, L5	$\lambda_{C1}, \lambda_{C5}$	1284.5	1291	1297.5	nm	
Wavelength L2, L6	$\lambda_{C2}, \lambda_{C6}$	1304.5	1311	1317.5	nm	
Wavelength L3, L7	$\lambda_{C3}, \lambda_{C7}$	1324.5	1331	1337.5	nm	
Side Mode Suppression Ratio	SMSR	30	-	-	dB	
Total average launch power	AOP <sub>T</sub>	-	-	10.4	dBm	
Average Launch Power, each lane	AOP <sub>L</sub>	-3.2	-	4.4	dBm	1
Outer Optical Modulation Amplitude (OMA <sub>outer</sub> ), each Lane for TDECQ < 1.4 dB for 1.4 dB ≤ TDECQ ≤ 3.4 dB	T <sub>OMA</sub>	-0.2 -1.6 + TDECQ	-	3.7	dBm	
Difference in launch power between any two lanes (OMA <sub>outer</sub> )	AOP <sub>d</sub>	-	-	3.9	dB	
Transmitter and Dispersion Eye Closure for PAM4 (TDECQ), each lane	TDECQ	-	-	3.4	dB	
Transmitter eye closure for PAM4 (TECQ), each lane	TECQ	-	-	3.4	dB	
TDECQ – TECQ	-	-	-	2.5	dB	
Over/under-shoot	-	-	-	22	%	
Transmitter power excursion	-	-	-	1.8	dBm	
Average Launch Power of OFF Transmitter, each lane	T <sub>OFF</sub>	-	-	-16	dBm	
Extinction Ratio	ER	3.5	-	-	dB	

Transmitter transition time (max)	Tr	-	-	17	ps	
RIN <sub>17.1OMA</sub> (max)	RIN	-	-	-136	dB/Hz	
Optical Return Loss Tolerance	ORL	-	-	17.1	dB	
Transmitter Reflectance	T <sub>R</sub>	-	-	-26	dB	2

Note 1: Average launch power, each lane (min) is informative and not the principal indicator of signal strength

Note 2: Transmitter reflectance is defined looking into the transmitter

**Table 2 – Receiver Optical Specifications**

Parameter	Symbol	Min.	Typical	Max.	Unit	Notes
Wavelength L0, L4	$\lambda_{C0}, \lambda_{C4}$	1264.5	1271	1277.5	nm	
Wavelength L1, L5	$\lambda_{C1}, \lambda_{C5}$	1284.5	1291	1297.5	nm	
Wavelength L2, L6	$\lambda_{C2}, \lambda_{C6}$	1304.5	1311	1317.5	nm	
Wavelength L3, L7	$\lambda_{C3}, \lambda_{C7}$	1324.5	1331	1337.5	nm	
Damage Threshold, each Lane	AOP <sub>D</sub>	5.4	-	-	dBm	
Average Receive Power, each Lane	AOP <sub>R</sub>	-7.2	-	4.4	dBm	
Receive Power (OMA <sub>outer</sub> ), each Lane	OMA <sub>R</sub>	-	-	3.7	dBm	
Difference in receive power between any two lanes (OMA <sub>outer</sub> ) (max)	AOP <sub>g</sub>	-	-	4.1	dB	
Receiver Reflectance	RR	-	-	-26	dB	
Receiver sensitivity (OMA <sub>outer</sub> ), each lane for TECQ < 1.4 dB for 1.4 dB ≤ TECQ ≤ 3.4 dB	S <sub>OMA</sub>	-	-	-4.6 -6 + TECQ	dBm	
Stressed Receiver Sensitivity (OMA <sub>outer</sub> ), each Lane	SRS	-	-	-2.6	dBm	1
Conditions of stressed receiver sensitivity test						
Stressed eye closure for PAM4 (SECQ), lane under test	-	-	3.4	-	dB	
OMA <sub>outer</sub> of each aggressor lane	-	-	1.4	-	dBm	

Note 1: Measured with conformance test signal at TP3 for the BER = 2.4x10<sup>-4</sup>.

## Ordering Information

**Table 3 - Ordering Information**

Part No.	Application	Data Rate	Laser Source	Fiber Type
CL800GOSFP2LR4-RHS	<b>2x400GBASE-LR4</b> <b>8x100GBASE-LR1</b>	<b>850Gb/s</b>	<b>EML</b>	<b>Single Mode Fiber</b>

## CONTACT:

Email: [sales@c-light.com](mailto:sales@c-light.com) <https://www.c-light.com>